

MOTOR DATA SHEET

Motor type: **3SIE280M4**

Series: **IE3**



26-04-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	90	125	S1	153	1491	576	2.6	3.0	8.4	94.9	95.5	95.4	0.78	0.86	0.89
690	Y	50	90	125	S1	89	1491	576	2.6	3.0	8.4	94.9	95.5	95.4	0.78	0.86	0.89

GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	77
Frame size	280	Sound power level [dB]	87
Number of poles	4	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6318C3
Frequency converter supply	yes	Bearing on ND-side	6318C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	761	Feet - material	cast iron
Moment of inertia [kgm ²]	1.8	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand