

MOTOR DATA SHEET

Motor type: **2Sg250M6_4**

Series: **MULTI SPEED**



26-04-2025

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|-----|-------|----|----|----|------|----|------|-----|------|------|------|------------------------|------|------|--------------------------|------|------|
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 400 | Y | 50 | 30 | 40 | S1 | 61 | 993 | 289 | 2.1 | 3.5 | 7.8 | 83.9 | 86.6 | 87.3 | 0.60 | 0.73 | 0.82 |
| 400 | Y | 50 | 45 | 60 | S1 | 80 | 1485 | 289 | 2.8 | 3.9 | 8.4 | 86.3 | 88.9 | 89.8 | 0.74 | 0.84 | 0.90 |

GENERAL DATA

| | | | |
|---------------------------------------|-------------|--------------------------------------|---------------|
| Efficiency class | - | Sound pressure level [dB] | 67 75 |
| Frame size | 250 | Sound power level [dB] | 77 85 |
| Number of poles | 6 4 | Terminal box position | on right side |
| Starting method | DOL / DOL | Possibility of terminal box rotation | yes |
| Insulation class | F | Bearing on D-side | 6315P63E1 |
| Frequency converter supply | on demand | Bearing on ND-side | 6315P63E1 |
| Mounting arrangement | IMB3/B5/B35 | Bearings regreasing | yes |
| Cooling method | IC411 | Housing - material | cast iron |
| Weight (IMB3) [kg] | 455 | Feet - material | cast iron |
| Moment of inertia [kgm ²] | 1.4 | Bearing shields - material | cast iron |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP55 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|-------|---------------------------------|-----------|
| Number of terminals or cables | 6 | Temperature sensors in bearings | on demand |
| Cable glands/inlets | 2 + 1 | Winding heaters | on demand |
| Temperature sensors in winding | yes | Optional accessories | on demand |

STANDARDS

IEC 60034-1

CERTIFICATES

on demand