

MOTOR DATA SHEET

Motor type: SIE200L8_6B-K

Series: MULTI SPEED



26-04-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	14.5	19.5	S1	35	740	187	2.8	3.1	6.1	78.7	82.9	84.2	0.47	0.61	0.71
400	Y	50	19	25.5	S1	36	982	185	1.6	2.2	5.4	87.3	88.1	87.3	0.75	0.84	0.87

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	62 61			
Frame size	200	Sound power level [dB]	72 71			
Number of poles	8 6	Terminal box position	on right side			
Starting method	DOL / DOL	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6312P63E1			
Frequency converter supply	on demand	Bearing on ND-side	6312P63E1			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	270	Feet - material	cast iron			
Moment of inertia [kgm2]	0.47	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2 + 1	Winding heaters	on demand			
Temperature sensors in winding	yes	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

