



## MOTOR DATA SHEET

Motor type: **Sg100L-6\_4B**

Series: **MULTI SPEED**

26-04-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	1.2	1.6	S1	3.2	960	11.94	1.8	2.7	4.8	66.4	71.6	73.0	0.52	0.64	0.74
400	Y	50	1.7	2.3	S1	4.1	1435	11.31	1.4	2.3	4.5	69.5	73.6	74.0	0.61	0.75	0.82

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	54 64
Frame size	100	Sound power level [dB]	74 71
Number of poles	6 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62062Z
Frequency converter supply	on demand	Bearing on ND-side	62062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	26	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.0094	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand