

## MOTOR DATA SHEET

Motor type: **Sg180L-4\_2**

Series: **MULTI SPEED**



26-04-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	17.5	23.6	S1	37	1480	112.92	3.0	3.2	8.0	84.7	87.7	88.5	0.55	0.68	0.77
400	YY	50	24	32.5	S1	43.7	2940	77.96	2.2	3.0	7.5	83.2	86.2	87.0	0.81	0.88	0.91

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	70 83
Frame size	180	Sound power level [dB]	76 82
Number of poles	4 2	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63112Z
Frequency converter supply	on demand	Bearing on ND-side	63112Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	175	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.173	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand