

MOTOR DATA SHEET

Motor type: Sh90-8_4S



26-04-2025

Series: MULTI SPEED

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	0.37	0.49	S1	1.75	690	5.12	1.6	2	2.4	-	-	72.0	-	-	0.85
400	YY	50	0.7	0.94	S1	1.75	1380	4.84	1.4	1.7	3.5	-	-	72.0	-	-	0.85

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	-		
Frame size	90	Sound power level [dB]	-		
Number of poles	8 4	Terminal box position	top		
Starting method	DOL / DOL	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	62052Z		
Frequency converter supply	on demand	Bearing on ND-side	62052Z		
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no		
Cooling method	IC411	Housing - material	aluminium		
Weight (IMB3) [kg]	10.8	Feet - material	aluminium		
Moment of inertia [kgm2]	0.0024	Bearing shields - material	aluminium		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP 54/IP 55	Climatic execution	U/2		

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY					
Number of terminals or cables	6				
	STAN	DARDS			

STANDARDS
IEC 60034-1
CERTIFICATES
on demand



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com