

## **MOTOR DATA SHEET**

Motor type: ESg213T-4



-

Series:	NEMA	EPACT	
---------	------	-------	--

26-04	4-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at lo	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	5.5	7.5	cont.	9	1750		2	2.8	6.9	89.5	90.2	89.5			

GENERAL DATA							
Efficiency class	NEMA EPACT	Frame size	213				
Number of poles	4	Insulation class	F				
Frequency converter supply	on demand	Cooling method	IC411				
Direction of rotation	CW/CCW	Painting	RAL5010				
Climatic execution	Ν						

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Optional accessories on demand						
STANDARDS						
NEMA MG-1						
CERTIFICATES						

ADDITIONAL INFO							
NEMA code letter	Н						

CSA

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com

