



MOTOR DATA SHEET

Motor type: **2SIE71-2B**

Series: **IE2**

21-01-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
230	Δ	50	0.55	0.75	S1	2.50	2820	1.86	3.0	3.0	4.7	70.0	74.0	75.0	0.51	0.64	0.73
400	Y	50	0.55	0.75	S1	1.45	2820	1.86	3.0	3.0	4.7	70.0	74.0	75.0	0.51	0.64	0.73

GENERAL DATA

Efficiency class	IE2	Sound pressure level [dB]	60
Frame size	71	Sound power level [dB]	67
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62032Z
Frequency converter supply	yes	Bearing on ND-side	62032Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	6.3	Feet - material	aluminium
Moment of inertia [kgm ²]	0.00053	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP54/IP55	Climatic execution	U/2

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	no
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand