

## MOTOR DATA SHEET

Motor type: **3SIE450H2D**

Series: **IE3**



05-05-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
690	Δ or Y	50	900	1200	S1	888	2990	2875	0.7	2.7	6.6	95.9	96.4	96.4	0.80	0.86	0.88

### GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	85
Frame size	450	Sound power level [dB]	-
Number of poles	2	Terminal box position	top
Starting method	direct or VSD	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6318 C3
Frequency converter supply	yes	Bearing on ND-side	6318 C3
Mounting arrangement	IMB3/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	4480	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	19.0	Bearing shields - material	cast iron
Direction of rotation	according to the order	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)
Cable glands/inlets	3	Winding heaters	on demand
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand