

MOTOR DATA SHEET

Motor type: **3SIE500H6A**

Series: **IE3**



04-12-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
690	Δ or Y	50	800	1080	S1	808	995	7678	0.9	2.4	5.8	95.5	96.2	96.3	0.74	0.83	0.86

GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	80
Frame size	500	Sound power level [dB]	-
Number of poles	6	Terminal box position	top/ * side
Starting method	direct or VSD	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	NU226 +6226 C3/* 6326 C3
Frequency converter supply	yes	Bearing on ND-side	NU226 /* 7326 BTVP or QJ326N2MPA
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	6200	Feet - material	cast iron
Moment of inertia [kgm ²]	61.5	Bearing shields - material	cast iron
Direction of rotation	according to the order	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)
Cable glands/inlets	3	Winding heaters	on demand
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand