

MOTOR DATA SHEET

Motor type: 2SIE71-8B

Series: **IE2**



04-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	Δ	50	0.12	0.17	S1	1.15	670	1.71	2.2	2.0	1.9	31.8	40.2	45.0	0.43	0.51	0.59
400	Y	50	0.12	0.17	S1	0.65	670	1.71	2.2	2.0	1.9	31.8	40.2	45.0	0.43	0.51	0.59

GENERAL DATA						
Efficiency class	IE2	Sound pressure level [dB]	50			
Frame size	71	Sound power level [dB]	57			
Number of poles	8	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	62032Z			
Frequency converter supply	yes	Bearing on ND-side	62032Z			
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no			
Cooling method	IC411	Housing - material	aluminium			
Weight (IMB3) [kg]	5.6	Feet - material	aluminium			
Moment of inertia [kgm2]	0.003882	Bearing shields - material	aluminium			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP54/IP55	Climatic execution	U/2			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	no			
Cable glands/inlets	1	Winding heaters	on demand			
Temperature sensors in winding	on demand	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

