

MOTOR DATA SHEET

Motor type: **ESg215T-6**

Series: **NEMA EPACT**



05-05-2025

| | | | | | | | ELECTI | RICAL | PARAN | 1ETER: | S | | | | | | |
|-----|-------|----|-----|----|-------|-----|--------|-------|-------|--------|------|--------|-------------|-------|------|---------------|---------|
| U | CONN. | f | ŀ | • | Duty | 1 | n | Т | TL/T | TB/T | IL/I | Effici | ency at loa | d [%] | Powe | r factor at l | oad [-] |
| V | - | Hz | kW | HP | - | Α | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 460 | | 60 | 3.7 | 5 | cont. | 6.6 | 1155 | | 1.9 | 2.5 | 6.1 | 87.2 | 88.4 | 87.5 | | | |

| GENERAL DATA | | | | | | |
|----------------------------|------------|------------------|---------|--|--|--|
| Efficiency class | NEMA EPACT | Frame size | 215 | | | |
| Number of poles | 6 | Insulation class | F | | | |
| Frequency converter supply | on demand | Cooling method | IC411 | | | |
| Direction of rotation | CW/CCW | Painting | RAL5010 | | | |
| Climatic execution | N | | | | | |

| ENVIRONMENTAL CONDITIONS | | | | | | | |
|--------------------------|-----------|------------------------------|------------|--|--|--|--|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 | | | | |
| Relative humidity [%] | up to 95 | | | | | | |

| ACCESSORY | | | | | | |
|----------------------|-----------|--|--|--|--|--|
| Optional accessories | on demand | | | | | |

| STANDARDS |
|-----------|
| NEMA MG-1 |

| CERTIFICATES | | | | | |
|--------------|-----|--|--|--|--|
| | CSA | | | | |

| NEMA code letter | Н | | |
|------------------|---|--|--|

