

MOTOR DATA SHEET

Motor type: **ESg254T-8**

Series: **NEMA EPACT**



04-12-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	ŀ	D	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Powe	r factor at lo	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460		60	3.7	5	cont.	7.2	880		1.6	2.4	5	84.2	85.8	85.5			

GENERAL DATA						
Efficiency class	NEMA EPACT	Frame size	254			
Number of poles	8	Insulation class	F			
Frequency converter supply	on demand	Cooling method	IC411			
Direction of rotation	CW/CCW	Painting	RAL5010			
Climatic execution	N					

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Optional accessories	on demand					

STANDARDS
NEMA MG-1

CERTIFICATES					
	CSA				

	ADDITIONAL INFO					
NEMA code letter	G					

