



MOTOR DATA SHEET

Motor type: **dSg180M2-EP**

Series: **GENERAL PURPOSE**

22-11-2024

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
1000	Y	50	22	30	S1	15.6	2945	71	2.7	2.6	6.8	90.5	91.8	91.5	0.77	0.84	0.89

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	75
Frame size	180	Sound power level [dB]	85
Number of poles	2	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	63112Z
Frequency converter supply	on demand	Bearing on ND-side	63112Z
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight [kg]	210	Feet - material	cast iron
Moment of inertia [kgm ²]	0.07	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 100		

ACCESSORY			
Number of terminals or cables	3	Temperature sensors in bearings	1 x bimetal (D-side)
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	3 x bimetallic	Optional accessories	on demand

STANDARDS	
IEC 60034-1, IEC 60079-0, IEC 60079-1	

CERTIFICATES	
ATEX, EAC, BiH	

ADDITIONAL INFO		
Ex marking	I M2 Ex db I Mb / II2G Ex db IIA T5 Gb	