

MOTOR DATA SHEET

Motor type: (E)cSg160M2B-EP

Series: **FLAMEPROOF IE1**



04-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	15	20	S1	26.6	2920	49	2.1	2.2	6	89.5	90.5	89.5	0.83	0.88	0.91

GENERAL DATA						
Efficiency class	-	Sound pressure level [dB]	72			
Frame size	160	Sound power level [dB]	82			
Number of poles	2	Terminal box position	top			
Starting method	DOL	Possibility of terminal box rotation	no			
Insulation class	F Bearing on D-side		63092Z			
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	63092Z			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	158	Feet - material	cast iron			
Moment of inertia [kgm2]	0.05	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 100						

ACCESSORY							
Number of terminals or cables	3	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS						
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7						

CERTIFICATES
ATEX, EAC, BiH

ADDITIONAL INFO							
Ex marking	II 2G Ex db (eb) IIB Tb Gb						

