



## MOTOR DATA SHEET

Motor type: **SUDg132M-8A(S3-40%)**

Series: **FOR CRANES**

08-05-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y+Y	50	3	4	S3-40%	8.3	680	42.1	-	2.2	-	71.6	74.7	73.5	0.49	0.62	0.71

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	71
Frame size	132	Sound power level [dB]	60
Number of poles	8	Terminal box position	top
Starting method	DOL with external starter	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	6308 2Z
Frequency converter supply	on demand	Bearing on ND-side	6308 2Z
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	90	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.053	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP44	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	3+3	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### ADDITIONAL INFO

Rotor voltage [V]	135	Rotor current [A]	13.5
Rotor resistance [ohm]	5.77	Additional rotor resistance [ohm]	0.053