

MOTOR DATA SHEET

Motor type: 4SIE315M2A

Series: **IE4**



04-12-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ı	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	132	175	S1	218	2979	423	2.4	2.7	7.8	95.7	96.2	96.2	-	-	0.91
690	Y	50	132	175	S1	126	2979	423	2.4	2.7	7.8	95.7	96.2	96.2	-	-	0.91

GENERAL DATA							
Efficiency class	IE4	Sound pressure level [dB]	78				
Frame size	315	Sound power level [dB]	88				
Number of poles	2	Terminal box position	top				
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	6315C3				
Frequency converter supply	yes	Bearing on ND-side	6315C3				
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes				
Cooling method	IC411	Housing - material	cast iron				
Weight (IMB3) [kg]	1050	Feet - material	cast iron				
Moment of inertia [kgm2]	1.7	Bearing shields - material	cast iron				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	2 + 1	Winding heaters	on demand				
Temperature sensors in winding	3 x PTC	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

