

CONN.

-

Y

Y

f

Ηz

50

50

U

V

400

400

Р

kW

0.25

0.37

ΗP

0.33

0.50

S1

S1

0.9

1.4

900

1420

2.65

2.45

1.7

1.7

1.8

1.9

MOTOR DATA SHEET





-

-

0.72

0.74

60.0

60.0

-

Motor type: Sh71-6_4C

Series: Multi speed

											0	6-06-2025
ELECTRICAL PARAMETERS												
Duty	I	n	Т	TL/T	TB/T	IL/I	Efficiency at load [%]		Power	r factor at l	oad [-]	
-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4

-

-

-

_

2.5

3.3

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	-		
Frame size	71	Sound power level [dB]	-		
Number of poles	6 4	Terminal box position	top		
Starting method	DOL / DOL	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	62032Z		
Frequency converter supply	on demand	Bearing on ND-side	62032Z		
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no		
Cooling method	IC411	Housing - material	aluminium		
Weight (IMB3) [kg]	7.4	Feet - material	aluminium		
Moment of inertia [kgm2]	0.001221	Bearing shields - material	aluminium		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP 54/IP 55	Climatic execution	U/2		

ENVIRONMENTAL CONDITIONS						
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000			
Relative humidity [%]	up to 95					

ACCESSORY						
Number of terminals or cables	6					
STANDARDS						

CIANDANDO	
IEC 60034-1	
CERTIFICATES	
on demand	



As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com