



## MOTOR DATA SHEET

Motor type: **3SIE160M8B**

Series: **IE3**

27-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	5.5	7.5	S1	12.6	710	74.0	1.8	2.6	5.0	86.4	87.2	86.2	0.53	0.66	0.73
690	Y	50	5.5	7.5	S1	7.3	710	74.0	1.8	2.6	5.0	86.4	87.2	86.2	0.53	0.66	0.73

### GENERAL DATA

Efficiency class	IE3	Sound pressure level [dB]	50
Frame size	160	Sound power level [dB]	59
Number of poles	8	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092ZC3
Frequency converter supply	yes	Bearing on ND-side	63092ZC3
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	118	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.078	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand