

## **MOTOR DATA SHEET**

Motor type: **3SIE225M4C** 

Series: **IE3** 



06-06-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Efficiency at load [%] Power factor at load		oad [-]			
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	55	75	S1	98	1484	354	2.1	2.9	7.1	93.6	94.6	94.6	0.78	0.85	0.86
690	Y	50	55	75	S1	57	1484	354	2.1	2.9	7.1	93.6	94.6	94.6	0.78	0.85	0.86

GENERAL DATA						
Efficiency class	IE3	Sound pressure level [dB]	63			
Frame size	225	Sound power level [dB]	73			
Number of poles	4	Terminal box position	top			
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6313C3			
Frequency converter supply	yes	Bearing on ND-side	6313C3			
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight (IMB3) [kg]	431	Feet - material	cast iron			
Moment of inertia [kgm2]	0.66	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	N			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	6	Temperature sensors in bearings	on demand			
Cable glands/inlets	2 + 1	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

