



## MOTOR DATA SHEET

Motor type: **2SIE112M2**

Series: **IE2**

13-03-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	4.0	5.5	S1	7.7	2915	13.1	2.4	2.7	8.5	86.9	97.3	86.3	0.70	0.82	0.87
690	Y	50	4.0	5.5	S1	4.5	2915	13.1	2.4	2.7	8.5	86.9	97.3	86.3	0.70	0.82	0.87

### GENERAL DATA

Efficiency class	IE2	Sound pressure level [dB]	61
Frame size	112	Sound power level [dB]	74
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63062Z
Frequency converter supply	yes	Bearing on ND-side	63062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	33.5	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.006	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand