



## MOTOR DATA SHEET

Motor type: **2SIE180L4A**

Series: **IE2**

22-12-2024

### ELECTRICAL PARAMETERS

| U   | CONN. | f  | P  |    | Duty | I    | n    | T      | TL/T | TB/T | IL/I | Efficiency at load [%] |      |      | Power factor at load [-] |      |      |
|-----|-------|----|----|----|------|------|------|--------|------|------|------|------------------------|------|------|--------------------------|------|------|
|     |       |    | kW | HP |      |      |      |        |      |      |      | -                      | -    | -    | 2/4                      | 3/4  | 4/4  |
| 400 | Δ     | 50 | 30 | 40 | S1   | 54.6 | 1465 | 195.56 | 2.4  | 2.7  | 7.0  | 92.0                   | 92.7 | 92.3 | 0.72                     | 0.81 | 0.86 |
| 690 | Y     | 50 | 30 | 40 | S1   | 31.6 | 1465 | 195.56 | 2.4  | 2.7  | 7.0  | 92.0                   | 92.7 | 92.3 | 0.72                     | 0.81 | 0.86 |

### GENERAL DATA

|                                       |             |                                      |            |
|---------------------------------------|-------------|--------------------------------------|------------|
| Efficiency class                      | IE2         | Sound pressure level [dB]            | 75         |
| Frame size                            | 180         | Sound power level [dB]               | 88         |
| Number of poles                       | 4           | Terminal box position                | top        |
| Starting method                       | DOL or Y/Δ  | Possibility of terminal box rotation | yes        |
| Insulation class                      | F           | Bearing on D-side                    | 6311 2Z C3 |
| Frequency converter supply            | yes         | Bearing on ND-side                   | 6311 2Z C3 |
| Mounting arrangement                  | IMB3/B5/B35 | Bearings regreasing                  | on demand  |
| Cooling method                        | IC411       | Housing - material                   | cast iron  |
| Weight (IMB3) [kg]                    | 200         | Feet - material                      | cast iron  |
| Moment of inertia [kgm <sup>2</sup> ] | 0.185       | Bearing shields - material           | cast iron  |
| Direction of rotation                 | CW/CCW      | Painting                             | RAL5010    |
| Degree of protection                  | IP55        | Climatic execution                   | N          |

### ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

### ACCESSORY

|                                |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 6         | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 1         | Winding heaters                 | on demand |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand