



MOTOR DATA SHEET

Motor type: **2SIE200L2C**

Series: **IE2**

05-02-2025



ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	45	60	S1	78	2952	146	2.3	2.7	6.6	93.7	93.5	93.0	0.83	0.88	0.89
690	Y	50	45	60	S1	45	2952	146	2.3	2.7	6.6	93.7	93.5	93.0	0.83	0.88	0.89

GENERAL DATA			
Efficiency class	IE2	Sound pressure level [dB]	80
Frame size	200	Sound power level [dB]	90
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6312C3
Frequency converter supply	yes	Bearing on ND-side	6312C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	310	Feet - material	cast iron
Moment of inertia [kgm ²]	0.21	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY			
Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	