

## **MOTOR DATA SHEET**

Motor type: **2SIE355H6C** 

Series: **IE2** 



22-10-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	ŀ	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ or Y	50	315	420	S1	552	992	3033	1.9	2.2	7.0	95.6	95.9	95.7	0.77	0.84	0.86
690	Δ or Y	50	315	420	S1	319	992	3033	1.9	2.2	7.0	95.6	95.9	95.7	0.77	0.84	0.86

GENERAL DATA							
Efficiency class	IE2	Sound pressure level [dB]	78				
Frame size	355	Sound power level [dB]	-				
Number of poles	6	Terminal box position	top/ * side				
Starting method	DOL, Y/Δ or VSD	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	6322 C3				
Frequency converter supply	yes	Bearing on ND-side	6322 C3				
Mounting arrangement	IMB3/B35/V1*	Bearings regreasing	yes				
Cooling method	IC411	Housing - material	cast iron				
Weight (IMB3) [kg]	2370	Feet - material	cast iron				
Moment of inertia [kgm2]	12.7	Bearing shields - material	cast iron				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS								
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000					
Relative humidity [%]	up to 95							

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)				
Cable glands/inlets	2	Winding heaters	on demand				
Temperature sensors in winding	6 x Pt100 (2pcs./phase)	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

