



MOTOR DATA SHEET

Motor type: **PSg100L-6A**

Series: **IE1**

27-04-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
230	Δ	50	2.2	3.0	S1	9.4	925	22.71	1.8	1.9	4.3	75.3	76.8	75.0	0.56	0.70	0.78
400	Y	50	2.2	3.0	S1	5.4	925	22.71	1.8	1.9	4.3	75.3	76.8	75.0	0.56	0.70	0.78

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	61
Frame size	100	Sound power level [dB]	71
Number of poles	6	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6206 2Z C3
Frequency converter supply	yes	Bearing on ND-side	6206 2Z C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	21.8	Feet - material	aluminium
Moment of inertia [kgm ²]	0.01	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

IEC 60034-1

CERTIFICATES

on demand