

## **MOTOR DATA SHEET**

Motor type: **Sh71X-4C** 

Series: **IE1** 



09-05-2025

	ELECTRICAL PARAMETERS																	
U	,	CONN.	f	,	Þ	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	factor at l	oad [-]
V	/	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
23	30	Δ	50	0.55	0.75	S1	3.50	1360	3.86	2.5	2.4	3.0	62.9	68.2	70.0	0.39	0.51	0.62
40	00	Y	50	0.55	0.75	S1	2.00	1360	3.86	2.5	2.4	3.0	62.9	68.2	70.0	0.39	0.51	0.62

GENERAL DATA							
Efficiency class	-	Sound pressure level [dB]	56				
Frame size	71	Sound power level [dB]	63				
Number of poles	4	Terminal box position	top				
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	62032Z				
Frequency converter supply	yes	Bearing on ND-side	62032Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no				
Cooling method	IC411	Housing - material	aluminium				
Weight (IMB3) [kg]	7.2	Feet - material	aluminium				
Moment of inertia [kgm2]	0.001099	Bearing shields - material	aluminium				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP 54/IP 55	Climatic execution	U/2				

ENVIRONMENTAL CONDITIONS								
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000					
Relative humidity [%]	up to 95							

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	no				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	

