



## MOTOR DATA SHEET

Motor type: **Sh80-2A**

Series: **IE1**

04-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
230	Δ	50	0.75	1.0	S1	3.30	2800	2.56	2.7	2.6	4.5	73.5	75.3	76.0	0.56	0.70	0.80
400	Y	50	0.75	1.0	S1	1.90	2800	2.56	2.7	2.6	4.5	73.5	75.3	76.0	0.56	0.70	0.80

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	65
Frame size	80	Sound power level [dB]	72
Number of poles	2	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62042Z
Frequency converter supply	yes	Bearing on ND-side	62042Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	7.9	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.000829	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 54/IP 55	Climatic execution	U/2

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	no
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand