



## MOTOR DATA SHEET

Motor type: **2Sg250M8\_4z**

Series: **MULTI SPEED**

04-12-2024

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	37	50	S1	73	738	479	2.4	2.2	5.5	-	-	89.5	-	-	0.82
400	YY	50	53	71	S1	91	1478	342	2.1	2.5	6.7	-	-	90.3	-	-	0.93

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	-
Frame size	250	Sound power level [dB]	-
Number of poles	8 4	Terminal box position	on right side
Starting method	DOL or Y/Δ / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6315P63E1
Frequency converter supply	on demand	Bearing on ND-side	6315P63E1
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	450	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	1.5	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY			
Number of terminals or cables	9	Temperature sensors in bearings	on demand
Cable glands/inlets	2 + 1	Winding heaters	on demand
Temperature sensors in winding	yes	Optional accessories	on demand

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	