

## MOTOR DATA SHEET

Motor type: **PSg132M-12\_6**

Series: **MULTI SPEED**



06-06-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	1.8	2.4	S1	7.4	470	36.57	1.8	2.3	3.3	59.0	65.8	68.1	0.34	0.43	0.52
400	YY	50	4.0	5.5	S1	8.5	940	40.64	1.4	2.1	4.9	82.5	82.3	80.0	0.69	0.80	0.85

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	73 72
Frame size	132	Sound power level [dB]	70 80
Number of poles	12 6	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63082Z
Frequency converter supply	on demand	Bearing on ND-side	63082Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	79	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.025	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand