

MOTOR DATA SHEET

Motor type: **Sg132M-8_2**

Series: MULTI SPEED



22-10-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	,	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	1.1	1.5	S1	5.1	735	14.29	2.5	3.4	4.5	57.2	64.1	66.0	0.32	0.39	0.47
400	Y	50	4.0	5.4	S1	7.3	2945	12.97	1.7	2.2	8.7	84.0	84.1	83.6	0.88	0.91	0.94

GENERAL DATA							
Efficiency class	-	Sound pressure level [dB]	68 70				
Frame size	132	Sound power level [dB]	77 83				
Number of poles	8 2	Terminal box position	top				
Starting method	DOL / DOL	Possibility of terminal box rotation	yes				
Insulation class	F	Bearing on D-side	63082Z				
Frequency converter supply	on demand	Bearing on ND-side	63082Z				
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	on demand				
Cooling method	IC411	Housing - material	cast iron				
Weight (IMB3) [kg]	73	Feet - material	cast iron				
Moment of inertia [kgm2]	0.035	Bearing shields - material	cast iron				
Direction of rotation	CW/CCW	Painting	RAL5010				
Degree of protection	IP 55	Climatic execution	N				

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY							
Number of terminals or cables	6	Temperature sensors in bearings	on demand				
Cable glands/inlets	1	Winding heaters	on demand				
Temperature sensors in winding	on demand	Optional accessories	on demand				

STANDARDS
IEC 60034-1

CERTIFICATES	
on demand	

