



## MOTOR DATA SHEET

Motor type: **Sh80-6\_4A**

Series: **MULTI SPEED**

04-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Y	50	0.12	0.16	S1	0.8	960	1.19	1.7	2.6	2.5	-	-	42.0	-	-	0.55
400	Y	50	0.37	0.50	S1	1.2	1390	2.54	1.4	1.6	2.7	-	-	59.0	-	-	0.80

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	-
Frame size	80	Sound power level [dB]	-
Number of poles	6 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6204Z2
Frequency converter supply	on demand	Bearing on ND-side	6204Z2
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	7.5	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.001693	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 54/IP 55	Climatic execution	U/2

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6		
-------------------------------	---	--	--

### STANDARDS

IEC 60034-1
-------------

### CERTIFICATES

on demand
-----------