

## **MOTOR DATA SHEET**

Motor type: Sh90-8\_2L

Series: MULTI SPEED



22-10-2025

	ELECTRICAL PARAMETERS																
U	CONN.	f	F	•	Duty	1	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Powe	r factor at l	oad [-]
V	-	Hz	kW	HP	-	Α	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	0.25	0.33	S1	1.6	710	3.36	2.2	2.9	2.7	-	-	52.0	-	-	0.46
400	Y	50	0.9	1.21	S1	2.6	2850	3.02	1.6	2	3.6	-	-	65.0	-	-	0.81

GENERAL DATA					
Efficiency class	-	Sound pressure level [dB]	-		
Frame size	90	Sound power level [dB]	-		
Number of poles	8 2	Terminal box position	top		
Starting method	DOL / DOL	Possibility of terminal box rotation	yes		
Insulation class	F	Bearing on D-side	62052Z		
Frequency converter supply	on demand	Bearing on ND-side	62052Z		
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no		
Cooling method	IC411	Housing - material	aluminium		
Weight (IMB3) [kg]	13.3	Feet - material	aluminium		
Moment of inertia [kgm2]	0.0032	Bearing shields - material	aluminium		
Direction of rotation	CW/CCW	Painting	RAL5010		
Degree of protection	IP 54/IP 55	Climatic execution	U/2		

ENVIRONMENTAL CONDITIONS					
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000		
Relative humidity [%]	up to 95				

ACCESSORY				
Number of terminals or cables	6			

STANDARDS	
IEC 60034-1	

CERTIFICATES
on demand

