



## MOTOR DATA SHEET

Motor type: **Sh90L-8\_4**

Series: **MULTI SPEED**

06-06-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	0.55	0.75	S1	2.1	695	7.56	1.85	2.0	3	51.8	59.4	62.1	0.40	0.51	0.61
400	YY	50	1.0	1.36	S1	2.2	1380	6.92	1.45	2.0	3.9	78.2	78.5	74.7	0.72	0.84	0.88

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	54 64
Frame size	90	Sound power level [dB]	67 68
Number of poles	8 4	Terminal box position	top
Starting method	DOL / DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62052Z
Frequency converter supply	on demand	Bearing on ND-side	62052Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	16.6	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.0027	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand