



## MOTOR DATA SHEET

Motor type: **Sf560H10-E**

Series: **STANDARD EFFICIENCY**

07-06-2025

| ELECTRICAL PARAMETERS |       |    |     |      |      |      |     |       |      |      |      |                        |     |      |                          |     |      |
|-----------------------|-------|----|-----|------|------|------|-----|-------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| U                     | CONN. | f  | P   |      | Duty | I    | n   | T     | TL/T | TB/T | IL/I | Efficiency at load [%] |     |      | Power factor at load [-] |     |      |
| V                     | -     | Hz | kW  | HP   | -    | A    | rpm | Nm    | -    | -    | -    | 2/4                    | 3/4 | 4/4  | 2/4                      | 3/4 | 4/4  |
| 6000                  | Y     | 50 | 800 | 1080 | S1   | 96.7 | 596 | 12819 | 1.1  | 2.2  | 6    | -                      | -   | 96.0 | -                        | -   | 0.83 |

| GENERAL DATA                          |            |                                      |                  |
|---------------------------------------|------------|--------------------------------------|------------------|
| Efficiency class                      | -          | Sound pressure level [dB]            | -                |
| Frame size                            | 560        | Sound power level [dB]               | -                |
| Number of poles                       | 10         | Terminal box position                | on right side    |
| Starting method                       | DOL        | Possibility of terminal box rotation | yes              |
| Insulation class                      | F          | Bearing on D-side                    | NU232EM1+6232MC3 |
| Frequency converter supply            | on demand  | Bearing on ND-side                   | NU226EM1         |
| Mounting arrangement                  | IM1001(B3) | Bearings regreasing                  | yes              |
| Cooling method                        | IC611      | Housing - material                   | steel            |
| Weight (IMB3) [kg]                    | 6620       | Feet - material                      | steel            |
| Moment of inertia [kgm <sup>2</sup> ] | 180        | Bearing shields - material           | steel            |
| Direction of rotation                 | CW/CCW     | Painting                             | RAL5010          |
| Degree of protection                  | IP55       | Climatic execution                   | N                |

| ENVIRONMENTAL CONDITIONS |                    |                              |            |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95           |                              |            |

| ACCESSORY                      |                          |                                 |                          |
|--------------------------------|--------------------------|---------------------------------|--------------------------|
| Number of terminals or cables  | 3                        | Temperature sensors in bearings | 2 x Pt100 (1 pc/bearing) |
| Cable glands/inlets            | 1                        | Winding heaters                 | on demand                |
| Temperature sensors in winding | 6 x Pt100 (2 pcs./phase) | Optional accessories            | on demand                |

| STANDARDS  |  |
|------------|--|
| IEC60034-1 |  |

| CERTIFICATES |  |
|--------------|--|
| on demand    |  |