



MOTOR DATA SHEET

Motor type: **Sh500H4C**

Series: **HIGH EFFICIENCY**

26-12-2024

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
6000	Y	50	1120	1500	S1	126	1494	7159	0.7	2.3	6.5	-	-	97.5	-	-	0.88

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	83
Frame size	500	Sound power level [dB]	-
Number of poles	4	Terminal box position	top/ * side
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	NU226EM1+6226MC3 / *6326MC3
Frequency converter supply	on demand	Bearing on ND-side	NU226EM1/*QJ326N2MPA
Mounting arrangement	B3/B35/V1*	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	6400	Feet - material	cast iron
Moment of inertia [kgm ²]	54	Bearing shields - material	cast iron
Direction of rotation	CW or CCW (according to the order)	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY			
Number of terminals or cables	3	Temperature sensors in bearings	2 x Pt100 (1 pc/bearing)
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	6 x Pt100 (2 pcs./phase)	Optional accessories	on demand

STANDARDS	
IEC 60034-1	

CERTIFICATES	
on demand	