



## MOTOR DATA SHEET

Motor type: **SIE256T6**

Series: **NEMA PREMIUM**

24-02-2026

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460	Δ	60	7.5	10	cont.	13.4	1180	60.3	3.5	3.3	7	89.2	90.8	91.0	0.58	0.70	0.77

GENERAL DATA			
Efficiency class	NEMA PREMIUM	Sound pressure level [dB]	-
Frame size	256	Sound power level [dB]	-
Number of poles	6	Terminal box position	left side
Starting method	DOL, PWS	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63092ZC3
Frequency converter supply	on demand	Bearing on ND-side	63092ZC3
Mounting arrangement	IMB3/IMB35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight [Lbs]	363	Feet - material	cast iron
Moment of inertia [Lb-Ft <sup>2</sup> ]	3.31	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY			
Number of terminals or cables	12	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS	
NEMA MG-1	

CERTIFICATES	
CSA	

ADDITIONAL INFO			
NEMA design	A	NEMA code letter	J