

MOTOR DATA SHEET

Motor type: SIE447TS2A



07-06-2025

Series: **NEMA PREMIUM**

ELECTRICAL PARAMETERS																	
U	CONN.	f	ŀ	D	Duty	I	n	Т	TL/T	TB/T	IL/I	Effici	ency at loa	d [%]	Power	r factor at le	oad [-]
V	-	Hz	kW	HP	-	А	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
460	Δ	60	150	200	cont.	211	3578	398.6	1.5	2.5	7.1	95.7	95.8	95.4	0.88	0.92	0.93

GENERAL DATA						
Efficiency class	NEMA PREMIUM	Sound pressure level [dB]	91			
Frame size	447	Sound power level [dB]	101			
Number of poles	2	Terminal box position	left side			
Starting method	DOL, PWS	Possibility of terminal box rotation	yes			
Insulation class	F	Bearing on D-side	6315C3			
Frequency converter supply	on demand	Bearing on ND-side	6315C3			
Mounting arrangement	IMB3/IMB35	Bearings regreasing	yes			
Cooling method	IC411	Housing - material	cast iron			
Weight [Lbs]	2161	Feet - material	cast iron			
Moment of inertia [Lb-Ft2]	29.1	Bearing shields - material	cast iron			
Direction of rotation	CW/CCW	Painting	RAL5010			
Degree of protection	IP55	Climatic execution	Ν			

ENVIRONMENTAL CONDITIONS							
Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000				
Relative humidity [%]	up to 95						

ACCESSORY						
Number of terminals or cables	12	Temperature sensors in bearings	on demand			
Cable glands/inlets	2	Winding heaters	on demand			
Temperature sensors in winding	3 x PTC	Optional accessories	on demand			

STANDARDS						
NEMA MG-1						
CERTIFICATES						
CSA						

ADDITIONAL INFO							
NEMA design	В	NEMA code letter	G				

As part of our development program, we reserve the rights to alter or amend any of the specifications without giving prior notice.

Copyright © 2025 Cantoni Group www.cantonigroup.com

