



## MOTOR DATA SHEET

Motor type: **STe445TS**

Series: **NEMA EPACT**

09-05-2025

### ELECTRICAL PARAMETERS

| U   | CONN. | f  | P   |     | Duty  | I   | n    | T   | TL/T | TB/T | IL/I | Efficiency at load [%] |      |      | Power factor at load [-] |     |     |
|-----|-------|----|-----|-----|-------|-----|------|-----|------|------|------|------------------------|------|------|--------------------------|-----|-----|
| V   | -     | Hz | kW  | HP  | -     | A   | rpm  | Nm  | -    | -    | -    | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4 | 4/4 |
| 460 | Δ     | 60 | 110 | 150 | cont. | 160 | 3569 | 300 | 1.8  | 2.15 | 6.5  | 95.7                   | 96.0 | 95.4 | 89.5                     | 92  | 92  |

### GENERAL DATA

|   |            |                                      |           |
|---|------------|--------------------------------------|-----------|
| Efficiency class                        | NEMA EPACT | Sound pressure level [dB]            | 82        |
| Frame size                              | 445        | Sound power level [dB]               | 92        |
| Number of poles                         | 2          | Terminal box position                | left side |
| Starting method                         | DOL, PWS   | Possibility of terminal box rotation | yes       |
| Insulation class                        | F          | Bearing on D-side                    | 6315C3    |
| Frequency converter supply              | on demand  | Bearing on ND-side                   | 6315C3    |
| Mounting arrangement                    | IMB3/IMB35 | Bearings regreasing                  | yes       |
| Cooling method                          | IC411      | Housing - material                   | cast iron |
| Weight [Lbs]                            | 1407       | Feet - material                      | cast iron |
| Moment of inertia [Lb-Ft <sup>2</sup> ] | 20.7       | Bearing shields - material           | cast iron |
| Direction of rotation                   | CW/CCW     | Painting                             | RAL5010   |
| Degree of protection                    | IP55       | Climatic execution                   | N         |

### ENVIRONMENTAL CONDITIONS

|                          |           |                              |            |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95  |                              |            |

### ACCESSORY

|                                |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 12        | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 2         | Winding heaters                 | on demand |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

### STANDARDS

NEMA MG-1

### CERTIFICATES

CSA

### ADDITIONAL INFO

|             |   |                  |   |
|-------------|---|------------------|---|
| NEMA design | B | NEMA code letter | G |
|-------------|---|------------------|---|