



MOTOR DATA SHEET

Motor type: **3SGf250M6-E**

Series: **FOR MINING CONVEYOR BELT DRIVES 3SGF SERIES**

23-12-2024

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
500	Y	50	45	60	S1/S4	64	980	439	2.6	2	6.6	92.8	92.8	92.0	0.81	0.86	0.88

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	66
Frame size	250	Sound power level [dB]	76
Number of poles	6	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	NU 315
Frequency converter supply	on demand	Bearing on ND-side	6315 C3
Mounting arrangement	IMB35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	steel
Weight (IMB3) [kg]	575	Feet - material	steel
Moment of inertia [kgm ²]	1.05	Bearing shields - material	cast iron
Direction of rotation	CW/CWW	Painting	RAL5010
Degree of protection	IP56	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY			
Number of terminals or cables	3	Temperature sensors in bearings	2 x bimetallic (1pc/bearing)
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x bimetallic	Optional accessories	on demand

STANDARDS	
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7	

CERTIFICATES	
ATEX, EAC, BiH	

ADDITIONAL INFO		
Ex marking	IM2 Ex db I Mb	