



## MOTOR DATA SHEET

Motor type: **ExSh90S-6-3GT4**

Series: **NON SPARKING**

22-12-2024

| ELECTRICAL PARAMETERS |       |    |      |      |      |   |     |      |      |      |      |                        |      |      |                          |      |      |
|-----------------------|-------|----|------|------|------|---|-----|------|------|------|------|------------------------|------|------|--------------------------|------|------|
| U                     | CONN. | f  | P    |      | Duty | I | n   | T    | TL/T | TB/T | IL/I | Efficiency at load [%] |      |      | Power factor at load [-] |      |      |
| V                     | -     | Hz | kW   | HP   | -    | A | rpm | Nm   | -    | -    | -    | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4  | 4/4  |
| 400                   | Y     | 50 | 0.65 | 0.88 | S1   | 2 | 935 | 6.64 | 2.3  | 2.6  | 4.1  | 65.1                   | 69.9 | 71.1 | 0.45                     | 0.57 | 0.68 |

| GENERAL DATA                          |                 |                                      |           |
|---------------------------------------|-----------------|--------------------------------------|-----------|
| Efficiency class                      | -               | Sound pressure level [dB]            | 53        |
| Frame size                            | 90              | Sound power level [dB]               | 63        |
| Number of poles                       | 6               | Terminal box position                | top       |
| Starting method                       | DOL             | Possibility of terminal box rotation | yes       |
| Insulation class                      | F               | Bearing on D-side                    | 62052Z    |
| Frequency converter supply            | on demand       | Bearing on ND-side                   | 62052Z    |
| Mounting arrangement                  | IMB3/B5/B35/B14 | Bearings regreasing                  | no        |
| Cooling method                        | IC411           | Housing - material                   | aluminium |
| Weight (IMB3) [kg]                    | 16              | Feet - material                      | aluminium |
| Moment of inertia [kgm <sup>2</sup> ] | 0.002           | Bearing shields - material           | aluminium |
| Direction of rotation                 | CW/CCW          | Painting                             | RAL5010   |
| Degree of protection                  | IP55            | Climatic execution                   | N         |

| ENVIRONMENTAL CONDITIONS |                    |                              |            |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 95           |                              |            |

| ACCESSORY                      |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 6         | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 2         | Winding heaters                 | no        |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

| STANDARDS               |  |
|-------------------------|--|
| EN 60079-0, EN 60079-15 |  |

| CERTIFICATES |  |
|--------------|--|
| ATEX         |  |

| ADDITIONAL INFO |                         |  |
|-----------------|-------------------------|--|
| Ex marking      | II 3G ExnA IIC T3-T4 Gc |  |