



MOTOR DATA SHEET

Motor type: **ExSg100L-6-2GT4**

Series: **INCREASED SAFETY**

07-06-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	1.2	1.6	S1	3.2	950	12.1	2.3	2.7	6.2	68.3	72.7	73.7	0.53	0.65	0.74

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	54
Frame size	100	Sound power level [dB]	64
Number of poles	6	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62062Z
Frequency converter supply	no	Bearing on ND-side	62062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	22.1	Feet - material	aluminium
Moment of inertia [kgm ²]	0.009	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

EN 60079-0, EN 60079-15

CERTIFICATES

ATEX

ADDITIONAL INFO

tE heating time up to T4 temperature [s]	12	Ex marking	II 2G Ex eb IIC T4
--	----	------------	--------------------