



MOTOR DATA SHEET

Motor type: **ExSg112M-4-2GT3**

Series: **INCREASED SAFETY**

15-03-2025

ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
			kW	HP								-	-	-	2/4	3/4	4/4
400	Δ	50	4	5.5	S1	8.3	1430	26.7	2.5	3	5.3	81.1	83.0	82.6	0.66	0.78	0.85

GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	62
Frame size	112	Sound power level [dB]	72
Number of poles	4	Terminal box position	top
Starting method	DOL or Y/Δ	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	63062Z
Frequency converter supply	no	Bearing on ND-side	63062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	33	Feet - material	aluminium
Moment of inertia [kgm ²]	0.014	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	no
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS

EN 60079-0, EN 60079-15

CERTIFICATES

ATEX

ADDITIONAL INFO

tE heating time up to T3 temperature [s]	7	Ex marking	II 2G Ex eb IIC T3
--	---	------------	--------------------