



## MOTOR DATA SHEET

Motor type: **(E)cSg160M4-EP**

Series: **FLAMEPROOF IE1**

05-01-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	11	15	S1	21.1	1463	72	2.5	2.9	7.5	88.5	89.2	89.5	0.68	0.79	0.84

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	66
Frame size	160	Sound power level [dB]	76
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	63092Z
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	63092Z
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	150	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.06	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 100		

ACCESSORY			
Number of terminals or cables	3	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS	
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7	

CERTIFICATES	
ATEX, EAC, BiH	

ADDITIONAL INFO		
Ex marking	II 2G Ex db (eb) IIB Tb Gb	