



MOTOR DATA SHEET

Motor type: **(E)cSgb280S2-EP**

Series: **FLAMEPROOF IE1**

05-01-2025

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	75	100	S1	128	2977	241	2.1	3.3	7.5	92.5	93.8	94.0	0.80	0.87	0.90

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	82
Frame size	280	Sound power level [dB]	92
Number of poles	2	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	NU315
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	6315C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	580	Feet - material	cast iron
Moment of inertia [kgm ²]	0.76	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 100		

ACCESSORY			
Number of terminals or cables	3	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS	
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7	

CERTIFICATES	
ATEX, EAC, BiH	

ADDITIONAL INFO		
Ex marking	II 2G Ex db eb IIB+H2 T5 Gb / II 2G Ex db IIB T5 Gb	