



## MOTOR DATA SHEET

Motor type: **(E)cSgb315M6A-EP**

Series: **FLAMEPROOF IE1**

05-01-2025

### ELECTRICAL PARAMETERS

| U   | CONN. | f  | P  |     | Duty | I   | n   | T   | TL/T | TB/T | IL/I | Efficiency at load [%] |      |      | Power factor at load [-] |      |      |
|-----|-------|----|----|-----|------|-----|-----|-----|------|------|------|------------------------|------|------|--------------------------|------|------|
| V   | -     | Hz | kW | HP  | -    | A   | rpm | Nm  | -    | -    | -    | 2/4                    | 3/4  | 4/4  | 2/4                      | 3/4  | 4/4  |
| 400 | Y     | 50 | 90 | 125 | S1   | 158 | 984 | 873 | 2.5  | 2    | 6.8  | 92.8                   | 93.8 | 93.7 | 0.79                     | 0.85 | 0.88 |

### GENERAL DATA

|                                       |                             |                                      |           |
|---------------------------------------|-----------------------------|--------------------------------------|-----------|
| Efficiency class                      | -                           | Sound pressure level [dB]            | 68        |
| Frame size                            | 315                         | Sound power level [dB]               | 78        |
| Number of poles                       | 6                           | Terminal box position                | top       |
| Starting method                       | DOL                         | Possibility of terminal box rotation | no        |
| Insulation class                      | F                           | Bearing on D-side                    | NU318     |
| Frequency converter supply            | on request - execution (-f) | Bearing on ND-side                   | 6318C3    |
| Mounting arrangement                  | IMB3/B5/B35                 | Bearings regreasing                  | yes       |
| Cooling method                        | IC411                       | Housing - material                   | cast iron |
| Weight (IMB3) [kg]                    | 815                         | Feet - material                      | cast iron |
| Moment of inertia [kgm <sup>2</sup> ] | 2.29                        | Bearing shields - material           | cast iron |
| Direction of rotation                 | CW/CCW                      | Painting                             | RAL5010   |
| Degree of protection                  | IP55                        | Climatic execution                   | N         |

### ENVIRONMENTAL CONDITIONS

|                          |                    |                              |            |
|--------------------------|--------------------|------------------------------|------------|
| Ambient temperature [°C] | from -20 up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%]    | up to 100          |                              |            |

### ACCESSORY

|                                |           |                                 |           |
|--------------------------------|-----------|---------------------------------|-----------|
| Number of terminals or cables  | 3         | Temperature sensors in bearings | on demand |
| Cable glands/inlets            | 1         | Winding heaters                 | on demand |
| Temperature sensors in winding | on demand | Optional accessories            | on demand |

### STANDARDS

IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7

### CERTIFICATES

ATEX, EAC, BiH

### ADDITIONAL INFO

|            |  |  |
|------------|--|--|
| Ex marking | II 2G Ex db eb IIB T4 Gb / II 2G Ex db IIB T4 Gb |  |
|------------|--|--|