



MOTOR DATA SHEET

Motor type: **(E)cSgb315S4-EP**

Series: **FLAMEPROOF IE1**

24-02-2026

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	110	150	S1	183	1480	710	2.3	2.2	6.9	94.1	94.4	94.2	0.86	0.90	0.92

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	76
Frame size	315	Sound power level [dB]	86
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	no
Insulation class	F	Bearing on D-side	NU318
Frequency converter supply	on request - execution (-f)	Bearing on ND-side	6318C3
Mounting arrangement	IMB3/B5/B35	Bearings regreasing	yes
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	785	Feet - material	cast iron
Moment of inertia [kgm ²]	1.67	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 100		

ACCESSORY			
Number of terminals or cables	3	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

STANDARDS	
IEC 60034-1, IEC 60079-0, IEC 60079-1, IEC 60079-7	

CERTIFICATES	
ATEX, EAC, BiH	

ADDITIONAL INFO	
Ex marking	II 2G Ex db eb IIB T4 Gb / II 2G Ex db IIB T4 Gb