



## MOTOR DATA SHEET

Motor type: **ExSg100L-4A-2GT3\_2D**

Series: **GAS AND DUST - CATEGORY 2D, 3D, 3G**

24-02-2026

ELECTRICAL PARAMETERS																	
U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Y	50	2.2	3	S1	5.2	1425	14.7	2.4	2.8	4.5	72.7	76.4	77.1	0.59	0.72	0.80

GENERAL DATA			
Efficiency class	-	Sound pressure level [dB]	60
Frame size	100	Sound power level [dB]	70
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62062Z
Frequency converter supply	no	Bearing on ND-side	62062Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	21.9	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.007	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP66	Climatic execution	N

ENVIRONMENTAL CONDITIONS			
Ambient temperature [°C]	from -20 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

ACCESSORY			
Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	2	Winding heaters	on demand
Temperature sensors in winding	3 x PTC	Optional accessories	on demand

STANDARDS	
EN 60034-1, EN 60079-0, EN 60079-7, EN 60079-15, EN 60079-31	

CERTIFICATES	
ATEX	

ADDITIONAL INFO		
Ex marking	II 2G Ex eb IIC T3 Gb / II 2D Ex tb IIIC T125°C Db	