



MOTOR DATA SHEET

Motor type: **SUDg355L10A(S3-60%)**

Series: **FOR CRANES**

06-06-2025

ELECTRICAL PARAMETERS

| U | CONN. | f | P | | Duty | I | n | T | TL/T | TB/T | IL/I | Efficiency at load [%] | | | Power factor at load [-] | | |
|-----|-------|----|----|-----|--------|-----|-----|------|------|------|------|------------------------|-----|------|--------------------------|-----|------|
| V | - | Hz | kW | HP | - | A | rpm | Nm | - | - | - | 2/4 | 3/4 | 4/4 | 2/4 | 3/4 | 4/4 |
| 380 | Δ | 50 | 86 | 115 | S3-60% | 190 | 586 | 1402 | - | 2.7 | - | - | - | 92.8 | - | - | 0.74 |

GENERAL DATA

| | | | |
|---------------------------------------|---------------------------|--------------------------------------|---------------|
| Efficiency class | - | Sound pressure level [dB] | - |
| Frame size | 355 | Sound power level [dB] | - |
| Number of poles | 10 | Terminal box position | on right side |
| Starting method | DOL with external starter | Possibility of terminal box rotation | no |
| Insulation class | F | Bearing on D-side | NU322EM1 |
| Frequency converter supply | no | Bearing on ND-side | 6322C3 |
| Mounting arrangement | IMB3 | Bearings regreasing | yes |
| Cooling method | IC411 | Housing - material | cast iron |
| Weight (IMB3) [kg] | 1560 | Feet - material | cast iron |
| Moment of inertia [kgm ²] | 10.6 | Bearing shields - material | cast iron |
| Direction of rotation | CW/CCW | Painting | RAL5010 |
| Degree of protection | IP54 | Climatic execution | N |

ENVIRONMENTAL CONDITIONS

| | | | |
|--------------------------|-----------|------------------------------|------------|
| Ambient temperature [°C] | up to +40 | Altitude above sea level [m] | up to 1000 |
| Relative humidity [%] | up to 95 | | |

ACCESSORY

| | | | |
|--------------------------------|---------|---------------------------------|-----------|
| Number of terminals or cables | 6+3 | Temperature sensors in bearings | on demand |
| Cable glands/inlets | 2 + 1 | Winding heaters | on demand |
| Temperature sensors in winding | 3 x PTC | Optional accessories | on demand |

STANDARDS

IEC 60034-1

ADDITIONAL INFO

| | | | |
|-------------------|-----|-------------------|-----|
| Rotor voltage [V] | 302 | Rotor current [A] | 172 |
|-------------------|-----|-------------------|-----|