

## MOTOR DATA SHEET

Motor type: **Sg160L-10**

Series: **ABOVE 8-POLES**



06-06-2025

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
400	Δ	50	5.5	7.5	S1	17.5	575	91.35	1.9	2.6	4.0	76.1	79.9	80.9	0.38	0.47	0.56
690	Y	50	5.5	7.5	S1	10.2	575	91.35	1.9	2.6	4.0	76.1	79.9	80.9	0.38	0.47	0.56

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	74
Frame size	160	Sound power level [dB]	62
Number of poles	10	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	6309 2Z C3
Frequency converter supply	yes	Bearing on ND-side	6309 2Z C3
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	cast iron
Weight (IMB3) [kg]	125	Feet - material	cast iron
Moment of inertia [kgm <sup>2</sup> ]	0.096	Bearing shields - material	cast iron
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP55	Climatic execution	N

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	6	Temperature sensors in bearings	on demand
Cable glands/inlets	1	Winding heaters	on demand
Temperature sensors in winding	on demand	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand