



## MOTOR DATA SHEET

Motor type: **SEh63-4CF**

Series: **SINGLE PHASE**

27-12-2024

### ELECTRICAL PARAMETERS

U	CONN.	f	P		Duty	I	n	T	TL/T	TB/T	IL/I	Efficiency at load [%]			Power factor at load [-]		
V	-	Hz	kW	HP	-	A	rpm	Nm	-	-	-	2/4	3/4	4/4	2/4	3/4	4/4
230	-	50	0.25	0.33	S1	1.9	1360	1.76	1.6	1.4	3.3	-	-	62.0	-	-	0.95

### GENERAL DATA

Efficiency class	-	Sound pressure level [dB]	-
Frame size	63	Sound power level [dB]	-
Number of poles	4	Terminal box position	top
Starting method	DOL	Possibility of terminal box rotation	yes
Insulation class	F	Bearing on D-side	62022Z
Frequency converter supply	-	Bearing on ND-side	62022Z
Mounting arrangement	IMB3/B5/B35/B14	Bearings regreasing	no
Cooling method	IC411	Housing - material	aluminium
Weight (IMB3) [kg]	5.2	Feet - material	aluminium
Moment of inertia [kgm <sup>2</sup> ]	0.00038	Bearing shields - material	aluminium
Direction of rotation	CW/CCW	Painting	RAL5010
Degree of protection	IP 54/IP 55	Climatic execution	U/2

### ENVIRONMENTAL CONDITIONS

Ambient temperature [°C]	from -15 up to +40	Altitude above sea level [m]	up to 1000
Relative humidity [%]	up to 95		

### ACCESSORY

Number of terminals or cables	4	Temperature sensors in bearings	no
Cable glands/inlets	1	Winding heaters	no
Temperature sensors in winding	no	Optional accessories	on demand

### STANDARDS

IEC 60034-1

### CERTIFICATES

on demand

### ADDITIONAL INFO

Run capacitor [mikroF/V]	10	Starting capacitor [mikroF/V]	20
--------------------------	----	-------------------------------	----